



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL FLEET 5W30 F.E.

A 100% synthetic, multigrade lubricant for gasoline and diesel engines

Applications:

Especially formulated to meet the latest demands in gasoline and diesel engines of heavy-duty vehicles, thereby offering excellent behaviour in engine systems with turbo-compressors and in multivalve and direct-injection systems.

Properties and advantages:

- Its fluidity at very low temperatures facilitates cold starts. It likewise guarantees extraordinary film resistance to high temperatures.
- Exceptional detergent, dispersant and anti-wear properties.
- It achieves greater friction reduction in comparison with standard lubricants, thereby providing a fuel savings, which also translates into decreased CO₂ emissions.

Quality level

API Service

CI4/CH4/CG4/CF4/CF/SL

ACEA

A3/B3/E3/E5/E7

Meets the following standards:

DB 229.1, 228.3

MAN 3275 – VOLVO VDS-3 – RENAULT RLD-2 – MACK
EO-N/EO-M PLUS – MTU TYPE 2

CUMMINS 20076/20077/20078

DETROIT DIESEL DDC 93K215 – IVECO applications

Technical characteristics:

SAE viscosity	5 W 30
Density at 15° C	0.86 g/cm ³
Viscosity at 40° C	70 cSt
Viscosity at 100° C	12 cSt
Viscosity index	170
Flash point	210° C
Freezing point	- 48° C
Total base number	16

The stated characteristics represent typical values.

Revision: 08/18

Advising with respect to the preparation and use of schedules for controlling and maintaining industrial plants and equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. may not be held liable for the legal actions that may arise from inadequate use of the product or products referenced herein, and in our judgement the information contained in the DESCRIPTIONS and APPLICATIONS is correct.

CERTIFIED COMPANY

